

4,8
Watt/m

IP 20

CRI>90

ta -20°÷ +45°C



up to
90 lm/w

100 mm 60 led/m

6 mm

Part Number	CCT (K)	Lumen/m	Ra	LED/m	V (Typ)	Cut	W/m	IP	EEC*
A413D2460027	2700K	380	92	60	24V/DC	100mm	4,8W	IP20	G
A413D246000W	3000K	380	93	60	24V/DC	100mm	4,8W	IP20	G
A413D246000N	4000K	420	92	60	24V/DC	100mm	4,8W	IP20	G
A413D246000B	6000K	400	92	60	24V/DC	100mm	4,8W	IP20	G

** The EEC specification refers in each case to the installed light source(s)



Datasheet download

- Strisce a LED 24V con piega angolare IP20**
- 60 led/m - 4,8W/m - LED3528
 - Superiore durata nel tempo, doppio rame rinforzato.
 - Possibile montaggio con pieghe a 90° o curve
 - Disponibile nei colori standard 2700K, 3000K, 4000K e 6000K
 - Fornite in nastro da 5m e cavetto

- 24V Flexible adhesive LED strips for corner bending IP20**
- 60 led/m - 4,8W/m - LED3528
 - High life time - Pcb in reinforced copper for better heat dissipation
 - Can be bent at 90° or similar curves
 - Available in standard colours 2700K, 3000K, 4000K and 6000K
 - Supplied in 5m reels with connecting cable

