



Part Number	Iout	Vout Led Min	Vout Led Max	W	Dimensions A x B x C	Protocol
A40CCBXL60DB	250÷750mA	30V	85V	60W	135 x 74 x 35	DALI / PUSH
A40CCBXH60DB	800÷1500mA	10V	48V	60W	135 x 74 x 35	DALI / PUSH

CCBXL60D

DIP	Io	Vo(min)	Vo(max)	Po(max)
0000	250mA	55V	85V	21W
0010	350mA	35V	85V	30W
0101	400mA	35V	85V	38W
0111	500mA	35V	85V	42W
1001	550mA	35V	85V	46W
1011	600mA	35V	85V	51W
1101	700mA	35V	85V	59W
1111	750mA	30V	80V	60W

CCBXH60D

DIP	Io	Vo(min)	Vo(max)	Po(max)
0001	800mA	25V	47V	37W
0011	900mA	20V	48V	43W
0101	1000mA	18V	48V	48W
0111	1100mA	18V	48V	52W
1001	1200mA	12V	48V	57W
1011	1300mA	10V	46V	60W
1100	1400mA	10V	42V	60W
1110	1500mA	10V	40V	60W



Datasheet download

Alimentatore Multicurrent - DALI & Push

- Alimentatore indipendente - IP20 - Classe II di isolamento - SELV
- Uscita in corrente costante regolabile con Dip-Switches:
A40CCBXL60DB: da 250 a 750mA, ±5%
A40CCBXH60DB: da 800 a 1500mA, ±5%,
- Comando della luce: DALI o pulsante sul lato primario
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Morsetti rapidi
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 200V ÷ 240V/AC - Uscita stabilizzata

Multicurrent Driver - DALI & Push

- For independent mounting - IP20 - Insulation class II - SELV
- Output in constant current settable by DIP-Switches:
A40CCBXL60DB: from 250 to 750mA, ±5%
A40CCBXH60DB: from 800 to 1500mA, ±5%,
- Light control by DALI or PUSH on the primry side
- Self-resetting protection against overtemperatures, open circuit and against output short circuits
- Fast terminals
- Cable clamp for flat and round cables
- Input voltage: 200V ÷ 240V/AC - Steady output



