

12÷14
Watt


CV+CC

PF
λ ≥ 0,6

IP 44



EMC





M

M

F


110

SELV


60 mm

ta -10°÷+40°C


AC/DC



Part Number	Iout	Vout Led Min	Vout Led Max@230V	Vout Led max @110V	Uout	W @230V	W @110V	Dimensions A x B x c
A40CPL11200B	350mA	2,75	40	31	45V	14W	11W	124 x 56 x 19
A40CPL20600B	500mA	2,75	21*	18*	24V	12W	9W	124 x 56 x 19
A40CPL30600B	700mA	2,75	21*	14*	24V	14W	10W	124 x 56 x 19

*in CC mode



Datasheet download

 Alimentatore per LED di potenza

- Alimentatore indipendente - IP44 - Classe II di isolamento
- Uscita in tensione e corrente costanti +/- 10%
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario
- Alimentazione : 110÷240V/AC- Uscita stabilizzata
- IP44 solo se fissaggio orizzontale e con 4 viti - Fornito senza cavi.

 Driver for High Brightness LEDs

- Independent driver - IP44 - Insulation class II
- Output in steady voltage and current +/- 10%
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits
- Input voltage: 110÷240V/AC- Steady output.
- IP44 only by horizontal installation with 4 screws - Supplied without cables.

