

23-36
Watt


CV

PF

$\lambda \geq 0,96$

IP 20



EMC













SELV



45 mm

$t_a -25^{\circ}\div +50^{\circ}\text{C}$



Part Number	Output V	Output Imax @ 230V	W @230V	Dimensions A x B x c
A40CV23W000B	24V	0,15A	23W	163 x 30 x 21
A40CV36W000B	24V	0,19A	36W	163 x 30 x 21



Datasheet download

 Alimentatore per LED di potenza

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Uscita in tensione costante, + /-5%
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario
- Doppio morsetto in ingresso
- Alto fattore di potenza
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione : 220÷240V/AC- Uscita stabilizzata

 Driver for High Brightness LEDs

- Independent driver - IP20 - Insulation class II
- Output in steady voltage, + /-5%
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits
- Double input terminal
- High power factor
- Cable clamp for flat and round cables
- Input voltage: 240÷240V/AC- Steady output.

