



144/288
Watt

IP 20

 $t_a -10^{\circ}\div +40^{\circ}\text{C}$ 

45 mm



A

B

Part Number	Input V	Output I max	Output V max	W	Dimensions A x B x C	Protocol
A40DALI1103B	12-24V/DC	12A	Vin-0,5V	144/288W	138 x 40 x 28,5	DALI/0-10V/1-10V/PUSH



input selector

1	2	3	Mode
OFF	OFF	X	DALI/Push 230V
OFF	ON	X	Push 12..24V
ON	OFF	X	0-10V
ON	ON	X	1-10V
X	X	OFF	PWM 250Hz
X	X	ON	PWM 3KHz



Datasheet download

Interfaccia DALI/0-10V/1-10V/Pulsante

- Comando DALI, pulsante, 0-10V, 1-10V o potenziometro, selezionabile tramite impostazione dip-switches.
- Alimentazione 24V/DC
- Comanda carichi resistivi fino a 12A
- Uscita PWM 250Hz o 3KHz
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti

DALI/0-10V/1-10V/Push interface

- Dimming control by DALI, PUSH, 0-10V, 1-10V signal or potentiometer, selecting the dipswitch combination on board.
- Input 24V/DC
- For resistive loads up to 12A
- PWM 250Hz or 3KHz output
- Cable clamp for flat and round cables



