


PDV Power Design 24V

Constant voltage LED driver / Alimentatore per LED a tensione costante

Made in Italy 



Part number Codice prodotto	P out W @230V	P out W @110V	V out DC + 5%	I out DC max @230V	I out DC max @110V	λ Power Factor	Efficiency @230V	Efficiency @110V	tc °C
A40PDV24000B	19	15	24	0,79 A	0,62 A	0,85	83%	80%	70

Features

- **IP20** independent driver
- Supplied with terminal cover and cable retainer
- Class II protection against electric shock for direct or indirect contact
- Self-resetting protection against overtemperatures, open circuit and output short circuits

Caratteristiche

- Alimentatore indipendente **IP20**
- Fornito di coprimorsetto e serracavo
- Protezione in classe II contro le scosse elettriche per contatti diretti e indiretti
- Protezione auto ripristinante contro le sovratemperature, il circuito aperto e il corto-circuito sul secondario

Directives / Direttive:

2014/35/EU (LVD); 2014/30/EU (EMC); RoHs 2011/65/EU + 2015/863/EU (RoHs); 2009/125/ ECODESIGN regulation (EU) N° 2019/2020 and 341/2021 amendment

Standards compliance: Conformità alle norme:

EN 61347-2-13:2014; EN 61347-2-13:2014 + A1:2017; EN 61347-1:2015
EN 61347-1:2015 + A1 :2021
EN IEC 55015:2019 + A11:2020; EN 61000-3-3:2014 + A1 :2020; EN 61547:2011;
EN IEC 61000-3-2:2019 + A1:2021 + A2:2024
EN 63000:2018;
EN IEC 62442-3:2022



PDV Power Design 24V

Constant voltage LED driver / Alimentatore per LED a tensione costante

Made in Italy 


Other electrical data	
Nominal input voltage AC	110-240 V
Input voltage DC	180-250 V
Mains frequency	50/60 Hz
Inrush current	14,9 A, 600 μ s
Surge capability (L-N)	> 1 kV
Nominal output voltage DC	24 V $\pm$ 5%
Output PWM frequency	1 kHz
Minimum output load	10 W
Output voltage ripple (100 Hz)	< 5%
Standby power (Psb)	$\leq$ 0,5 W
Networked stanby power (Pnet)	$\leq$ 0,5 W
No-load proof	YES
Intended for no-load operation	NO
Output PstLM (Flicker value)	$\leq$ 1
Output SVM (Stroboscopic effects value)	$\leq$ 0,4
Insulation primary/secondary:	Class II SELV 3750V AC
Leakage current:	< 0,5 mA
Temperatures and operating conditions	
Ambient temperature range	-10...+40 °C
Storage temperature range	-15...+50 °C
Capabilities	
Dimmable	NO
Protections	Open load, short-circuit, overload, overtemperature
Connections	
Cables cross-section (input side)	2 x 0,5-2,5 mm ² , 13-20 AWG
Wire preparation lenght (input side)	4...9 mm ²
Cables cross-section (output side)	2 x 0,5-2,5 mm ² , 13-20 AWG
Wire preparation lenght (output side)	4...9 mm ²
Nominal life-time	50000h @Ta 40 °C

PDV Power Design 24V

Constant voltage LED driver / Alimentatore per LED a tensione costante

Made in Italy 

Product dimensions



Product weight

A40PDV24000B	115 gr.
--------------	---------