

4,5/11
Watt/m

IP 20

CRI>80



ta -10°÷ +40°C



up to
145 lm/w

50 mm / 140 led/m
4 mm



33.3 mm / 210 led/m
4 mm



33.3 mm / 180led/m
4 mm



Part Number	CCT (K)	Lumen/m	Ra	LED/m	V (Typ)	Cut	W/m	IP	EEC*
A41F24144527	2700K	540	84	140	24V/DC	50mm	4,5W	IP20	E
A41F24144530	3000K	620	82	140	24V/DC	50mm	4,5W	IP20	E
A41F24144540	4000K	650	84	140	24V/DC	50mm	4,5W	IP20	E
A41F24210827	2700K	980	84	210	24V/DC	33,3mm	8W	IP20	E
A41F24210830	3000K	1080	82	210	24V/DC	33,3mm	8W	IP20	E
A41F24210840	4000K	1140	84	210	24V/DC	33,3mm	8W	IP20	E
A41F24181130	3000K	1070	92	180	24V/DC	33,3mm	11W	IP20	F

** The EEC specification refers in each case to the installed light source(s)



Datasheet download

Strisce flessibili a LED 24V autoadesive IP20

- 140 led/m - 4,5W/m - LED 2216
- 210 led/m - 8W/m - LED 2216
- 180 led/m - 11W/m - LED 2216
- Ultra slim: 4mm
- Ridotta spaziatura dei LED per una luce omogenea
- Disponibile nei colori standard 2700K, 3000K e 4000K
- Fornite in nastro da 5m e cavetto di raccordo.

24V Flexible adhesive LED strips IP20

- 140 led/m - 4,5W/m - LED 2216
- 210 led/m - 8W/m - LED 2216
- 180 led/m - 11W/m - LED 2216
- Ultra slim: 4mm
- Reduced space between diodes for homogeneous output light
- Color temperatures available: 2700K, 3000K and 4000K
- Supplied in 5m reels with connecting cable.

