

60
WattPF
 $\lambda \geq 0,96$


IP 20



EMC



SELV

 $t_a -10^{\circ}\div +40^{\circ}\text{C}$ DALI
Dimmable

Part Number	Output V	Output@230V I max	W @230V	Output@110V I max	W @110V	Dimensions A x B x C	Protocol
A40FB060D00B	24V/DC	2,5A	60W	1,25A	30W	116,5 x 75 x 20	DALI / PUSH
A40FB060010B	24V/DC	2,5A	60W	1,25A	30W	116,5 x 75 x 20	0-10V
A40FB060110B	24V/DC	2,5A	60W	1,25A	30W	116,5 x 75 x 20	1-10V



Datasheet download

Alimentatore LED compatto DALI/Push -0-10V - 1-10V

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Uscita in tensione costante 24VDC, $\pm 5\%$ PWM 1KHz
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario
- Alto fattore di potenza
- Basso spessore
- Alimentazione: 110 $\div$ 240V/AC - Uscita stabilizzata.

Compact LED Driver DALI/Push - 0-10V - 1-10V

- For independent use - IP20 - Insulation class II
- Steady voltage output 24VDC, $\pm 5\%$ PWM 1KHz
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits
- High power factor
- Reduced thickness
- Input voltage: 110 $\div$ 240V/AC - Steady output.



