



| Part Number  | Output V | Ouput I <sub>max</sub> | W   | Dimensions A x B x C | Protocol            | EN 05 |
|--------------|----------|------------------------|-----|----------------------|---------------------|-------|
| A40MDE03000B | 24V/DC   | 1,25A                  | 30W | 165 x 41 x 27,5      | TRIAC / IGBT/MOSFET |       |
| A40MDE06000B | 24V/DC   | 2,5A                   | 60W | 205 x 51 x 35        | TRIAC / IGBT/MOSFET | •     |



Datasheet download

## Alimentatore dimmerabile per moduli LED

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Regolazione della luce a taglio di fase con dimmer TRIAC, IGBT e MOSFET con minimo regolabile, compatibili con carichi LED
- Uscita in tensione costante 24VDC, +/-5%
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 220-240V/AC - Uscita stabilizzata.

## Dimmable driver for LED modules

- For independent use - IP20 - Insulation class II
- Light regulation by TRIAC, IGBT and MOSFET dimmers with settable minimum, compatible with LED loads
- Output in steady voltage 24VDC, +/-5%
- Self-resetting protection against overtemperatures against open circuit and against output short circuits.
- Cable clamp for flat and round cables
- Input voltage: 220-240V/AC - Steady output.

