

45-60
Watt


CV

SELV

PF
 $\lambda \geq 0,96$

IP 20



EMC





M

M

F

110

$t_a -10^{\circ} \div +40^{\circ}C$



62 mm


AC 50Hz


DC

On request





Part Number	Output V	Output@230V I typ	W	Output@110V I _{max}	W @110V	Dimensions A x B x C	Protocol	
A40MDR04501B	12V/DC	3,75A	45W	2,92A	35W	205 x 51 x 35	0-10V / PUSH	
A40MDR06001B	24V/DC	2,5A	60W	1,79A	43W	205 x 51 x 35	0-10V / PUSH	.



Datasheet download

 Alimentatore dimmerabile a LED

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Comando della luce - accensione, regolazione e spegnimento - con uno o più pulsanti
- Regolazione con potenziometro 470K o con segnale 0-10V
- Uscita in tensione costante PWM 300Hz $\pm 5\%$
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Alimentazione: 110V $\div$ 240V/AC - Uscita stabilizzata. A richiesta alimentazione a 230VDC.

 Dimmable driver for LED modules

- For independent use - IP20 - Insulation class II
- Light control - on, off and dimming - by one or more push-buttons
- Dimming by 470K potentiometer or signal 0-10V
- Light in steady voltage PWM 300Hz $\pm 5\%$
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits.
- Input voltage: 110V $\div$ 240V/AC - Steady output. On request, 230VDC input voltage.

