

49÷160
Watt

 CV

PF
 $\lambda \geq 0,96$

IP 65

 CE

EMC

 M

 M


 F

 110

SELV

$t_a -20^{\circ} \div +45^{\circ}C$

 90 mm



Part Number	Output V	Output I _{max} @ 230V	Output I _{max} @ 110V	W @230V	W @110V	Dimensions A x B x c
A40MIP05400N	12V	4,08A	3A	49W	36W	170 x 70 x 35
A40MIP11000N	12V	9,16A	5,9A	110W	70W	177 x 82 x 35
A40MIP07000N	24V	2,90A	2,08A	70W	50W	170 x 70 x 35
A40MIP16000N	24V	6,66A	2,90A	160W	70W	177 x 82 x 35



Datasheet download

 Alimentatore per LED di potenza

- Alimentatore da incorporare - IP65 - Classe II di isolamento
- Uscita in tensione costante 12÷24VDC, ±5%
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario
- Rifasatore attivo, forma compatta e basso riscaldamento
- Alimentazione: 110÷240V/AC - Uscita stabilizzata

 Driver for High Brightness LEDs

- To be built in - IP65 - Insulation class II
- Output in steady voltage 12÷24VDC, ±5%
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits.
- Active power factor correction, compact size and reduced heating
- Input voltage: 110÷240V/AC - Steady output.

