


Part Number	CCT (K)	Lumen/m	Ra	LED/m	V (Typ)	Cut	W/m	IP
A41N08080627	2700K	290	94	238	24VDC	Free	6W	IP67
A41N08080630	3000K	340	94	238	24VDC	Free	6W	IP67
A41N08080640	4000K	295	96	238	24VDC	Free	6W	IP67
A41KITN08080	Kit: 10x brackets with screws, 2x caps with hole, 4 x end caps, 2 x glue tubes							
A41FIXN08080	10 fixing brackets with 10 screws							
BAR0808AL100	1mt aluminum profile							



Datasheet download

Strisce flessibili a LED 24V IP67

- Dimensione ridotta 8x8mm
- Adatta anche per uso esterno (resistente ai raggi UV e alla nebbia salina)
- Movimento verticale (TOP) Ø>100mm, movimento orizzontale (SIDE) Ø>300mm
- 238 led/m - 6W/m - LED2216
- Taglio libero - Punto di saldatura per collegamento cavo ogni 29,4mm
- Disponibile nei colori standard: 2700K, 3000K e 4000K
- Fornite in nastro da 5m e cavetto di raccordo.
- Fornite con 10 clips, 10 viti, 2 tappi per ripartenza, 4 tappi chiusura e 2 tubetti di silicone



24V Flexible LED strips IP67

- Mini Size 8x8mm
- Suitable for outdoor installation too (UV resistant and salt-mist proof).
- Free bending: vertical (TOP) bending Ø>100mm, horizontal (SIDE) bending Ø>300mm
- 238 led/m - 6W/m - LED2216
- Free cutting - Soldering pad for wire connection every 29,4mm
- Color temperatures available: 2700K, 3000K and 4000K
- Supplied in 5m reels with connecting cable
- Supplied with 10 clips, 10 screws, 2 open caps for rewiring, 4 end caps and 2 silicon paste

