

60-100  
Watt

  
CV

  
SELV

PF

$\lambda \geq 0,98$

IP 20



EMC





M

M

F

110

$t_a$


$-10^{\circ} \div +40^{\circ}C$

  
AC 50Hz

DC

On request

  
63 mm



| Part Number  | Output<br>V | Output@230V<br>I max | W<br>@230V | Output@110V<br>I max | W<br>@110V | Dimensions A<br>x B x C | ENEC 05 |
|--------------|-------------|----------------------|------------|----------------------|------------|-------------------------|---------|
| A40PBS06000B | 24V/DC      | 2,5A                 | 60W        | 1.45A                | 35W        | 176x 55 x 30            | .       |
| A40PBS07500B | 24V/DC      | 3,12A                | 75W        | 2,10A                | 50W        | 176x 55 x 30            |         |
| A40PBS10000B | 24V/DC      | 4,16A                | 100W       | 2,10A                | 50W        | 176 x 55 x 30           | .       |



Datasheet download

 **Alimentatore LED**

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Uscita in tensione costante 24V PWM
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Morsetti rapidi
- Doppio morsetto d'uscita
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 110÷240V/AC - Uscita stabilizzata.
- A richiesta, alimentazione a 230VDC

 **LED Driver**

- For independent use - IP20 - Insulation class II
- Output in constant voltage 24V PWM
- Self-resetting protection against overtemperatures, open circuit and against output short circuits
- Fast terminals
- Double output.
- Cable clamp for flat and round cables
- Input voltage: 110÷240V/AC - Steady output.
- On request, 230VDC input voltage

