



Part Number	Output V	Ouput@230V I max	W @230V	Ouput@110V I max	W @110V	Dimensions A x B x C	Protocol
A40PBX75D48B	48V	1,56A	75W	1,04A	50W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH
A40PBX10D48B	48V	2,08A	100W	1,25A	60W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH
A40PBX15D48B	48V	3,12A	150W	1,25A	60W	210 x 75 x 35	DALI / 0-10V/1-10V/PUSH



Datasheet download

Alimentatore LED 48V dimmerabile DALI/0-10V/1-10V/Push

- Alimentatore indipendente - IP20 - Classe II di isolamento
 - Comando DALI o pulsante (sul secondario, con memoria), 0-10V, 1-10V o potenziometro, selezionabile tramite impostazione dip-switches.
 - Possibilità di sincronizzare più alimentatori
 - Uscita in tensione costante 48V PWM
 - Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
 - Morsetti rapidi
 - Doppio collegamento di uscita
 - Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
 - Alimentazione: 110÷240V/AC - Uscita stabilizzata.
- A richiesta, alimentazione a 230VDC o specifica potenziata a 110V

48V dimmable LED Driver DALI/0-10V/1-10V/Push

- For independent use - IP20 - Insulation class II
 - Dimming control by DALI or PUSH (on the secondary, with memory), 0-10V, 1-10V or potentiometer, selecting the dipswitch combination on board.
 - Possible synchronization of more drivers
 - Output in constant voltage 48V PWM
 - Self-resetting protection against overtemperatures, open circuit and against output short circuits
 - Fast terminals
 - Double output.
 - Cable clamp for flat and round cables
 - Input voltage: 110÷240V/AC - Steady output.
- On request, 230VDC input voltage or specific boosted 110V version

