

100
Watt

 CV

PF
λ ≥ 0,98

IP 20

CE

EMC

M

M

F

ta-10°÷ +40°C






 84 mm

DALI
Dimmable

 Dimmable



DALI DT8-TC



Part Number	Protocol	Output V	Output@230V I max	W @230V	W @110V	Dimensions A x B x C
A40PBX100TWB	DALI DT8-TC / PUSH	24V/DC	2 x 4,16A	100W+100W	60W+60W	210 x 75 x 35



Datasheet download

 Alimentatore Tunable White DALI DT8-TC/Push

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Comanda strisce Led a luce calda e fredda a due canali
- Comando DALI DT8-TC o pulsanti.
Pulsante 1: pressione rapida (ON/OFF), pressione prolungata (dimmerazione)
Pulsante 2: selezione della temperatura colore.
- Morsetti rapidi
- Alto fattore di potenza
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- No flicker
- Alimentazione: 100÷240 V / AC - Uscita stabilizzata.

 Driver for Tunable White control DALI DT8-TC/ Push

- Independent driver - IP20 - Insulation class II
- Control of 2-channel led strips (warm and cool light)
- Control by DALI DT8-TC or push-buttons
Push-button 1: short push (ON/OFF), long push (dimming)
Push-button 2: Tunable White
- Fast terminals
- High power factor
- Cable clamp for flat and round cables
- Flicker free
- Input Voltage: 100÷240 V/AC - Steady output.



