

8÷14
Watt

CV+CC

$\lambda \geq 0,5$
PF

IP 20

CE

EMC

M

M

F

110



SELV

39 mm

$t_a -10^{\circ} \div +40^{\circ}C$

AC/DC

05



Part Number	Iout	Vout Led Min	Vout Led Max@230V	Vout Led max @110V	Uout	W @230V	W @110V	Dimensions A x B x c	05
A40PLK18500B	185mA	2.75	43	43	45V	8W	8W	122 x 33 x 19	
A40PLK1131WB	240mA	2.75	43	35	45V	10W	8,4W	122 x 33 x 19	
A40PLK30000B	300mA	2.75	43	33	45V	13W	10W	122 x 33 x 19	
A40PLK1121WB	350mA	2.75	40	31	45V	14W	11W	122 x 33 x 19	.
A40PLK110Z0B	350mA	2.75	31	24	35V	11W	8,4W	122 x 33 x 19	
A40PLK20500B	500mA	2.75	23*	20*	24V	12W	10W	122 x 33 x 19	
A40PLK303Z0B	700mA	2.75	10,5*	10,5*	12V	8,4W	8,4W	122 x 33 x 19	
A40PLK3063WB	700mA	2.75	20*	14*	24V	14W	10W	122 x 33 x 19	.
A40PLK12000B	1080mA	-	-	-	12V	13W	10W	122 x 33 x 19	

* in CC mode



Datasheet download

Alimentatore per LED di potenza

- Alimentatore indipendente - IP 20 - Classe II di isolamento
- Uscita in corrente costante 185mA, 240mA, 300mA, 350mA, 500mA, 700mA
- Uscita a tensione costante 12÷24V/DC
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Alimentazione: 110÷240V/AC - Uscita stabilizzata

Driver for High Brightness LEDs

- Independent driver - IP20 - Insulation class II
- Output in constant current 185mA, 240mA, 300mA, 350mA, 500mA, 700mA
- Output in constant tension 12÷24V/DC
- Self-resetting protection against overtemperatures, open circuit and output short circuits.
- Input voltage: 110÷240V/AC - Steady output.

