

8,4÷15
Watt


CV+CC

PF
λ ≥ 0,6

IP 40



EMC












SELV



ta -10°÷ +40°C



Part Number	Iout	Vout Led Min	Vout Led Max@230V	Vout Led max @110V	Uout	W @230V	W @110V	Dimensions A x B x c	Housing
A40PLP10600N	350mA	2,75	21*	21*	24V	8,4W	8,4W	68 x 40 x 23	Black
A40PLP10600T	350mA	2,75	21*	21*	24V	8,4W	8,4W	68 x 40 x 23	Transparent
A40PLP10500N	500mA	2,75	21*	18*	24V	12W	9W	68 x 40 x 23	Black
A40PLP10500T	500mA	2,75	21*	18*	24V	12W	9W	68 x 40 x 23	Transparent
A40PLP30300N	700mA	2,75	10,5*	10,5*	12V	8,4W	8,4W	68 x 40 x 23	Black
A40PLP30300T	700mA	2,75	10,5*	10,5*	12V	8,4W	8,4W	68 x 40 x 23	Transparent
A40PLP30600N	700mA	2,75	21*	12*	24V	14W	9W	68 x 40 x 23	Black
A40PLP30600T	700mA	2,75	21*	12*	24V	14W	9W	68 x 40 x 23	Transparent
A40PLP11200N	350mA	2,75	42	26	45V	15W	9W	68 x 40 x 23	Black
A40PLP11200T	350mA	2,75	42	26	45V	15W	9W	68 x 40 x 23	Transparent
A40PLP12000N	1166mA max	-	-	-	12V	14W	9W	68 x 40 x 23	Black
A40PLP12000T	1166mA max	-	-	-	12V	14W	9W	68 x 40 x 23	Transparent

*in CC mode



Datasheet download

-  **Alimentatore per LED di potenza**
- Alimentatore indipendente - IP40 - Classe II di isolamento
 - Uscita in corrente costante 350÷700 mA, ±10% o tensione costante 12÷24V/DC
 - Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
 - Alimentazione: 110÷240V/AC - Uscita stabilizzata.
 - Cavo standard 2x0,75mm²: 100cm+50cm

-  **Driver for High Brightness LEDs**
- Independent driver - IP 40 - Insulation class II
 - Output in steady current: 350÷700 mA, ±10% or in constant tension 12÷24V/DC
 - Self-resetting protection against overtemperatures, open circuit and output short circuits.
 - Input voltage: 110÷240V/AC - Steady output.
 - Standard cable 2x0,75mm²: 100cm+50cm

