

PLV 48V - Slim Waterproof IP65

48V LED Components

100÷150
Watt

 CV

PF
 $\lambda \geq 0,96$

IP 65

 CE

EMC



 M

 M

 F


 110

SELV



 60 mm

$t_a -10^{\circ} \div +45^{\circ}C$



Part Number	Output V	Ouput Imax	W	Dimensions A x B x c
A40PLV10048B	48V	2,08A	100W	175 x 50 x 32
A40PLV15048B	48V	3,12A	150W	175 x 50 x 32



Datasheet download

Alimentatore 48V per LED di potenza - IP65

- Alimentatore da incorporare - IP65 - Classe II di isolamento
- Uscita in tensione costante 48VDC, $\pm 5\%$
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario
- Alimentazione: 220÷240V/AC $\pm 10\%$ - Uscita stabilizzata

Driver 48V for High Brightness LEDs - IP65

- To be built in - IP65 - Insulation class II
- Output in steady voltage 48VDC, $\pm 5\%$
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits.
- Input voltage: 220÷240V/AC $\pm 10\%$ - Steady output.