

8-14,4
Watt


CV+CC

PF

$\lambda \geq 0,5$

IP 65



EMC














SELV



$t_a -20^{\circ}\div +45^{\circ}\text{C}$





Part Number	Iout	Vout Led Min	Vout Led Max@230V	Vout Led max @110V	Uout	W @230V	W @110V	Dimensions A x B x c	
A40PRL18500B	185mA	2,75	43	43	45V	8W	8W	110 x 33 x 21	
A40PRL30000B	300mA	2,75	43	33	45V	13W	10W	110 x 33 x 21	
A40PRL11200B	350mA	2,75	40	31	45V	14W	11W	110 x 33 x 21	.
A40PRL30600B	700mA	2,75	21*	14*	24V	14W	10W	110 x 33 x 21	.
A40PRL12000B	1200mA	-	-	-	12V	14,4W	10W	110 x 33 x 21	

* in CC mode



Datasheet download

 Alimentatore per LED di potenza

- Alimentatore da incorporare - IP65 - Classe II di isolamento
- Uscita in corrente costante 350÷700 mA, ±5%
- Uscita in tensione costante, ±5%
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Alimentazione: 110÷240V/AC - Uscita stabilizzata.

 Driver for High Brightness LEDs

- To be built in - IP 65 - Insulation class II
- Output in steady current: 350÷700 mA, ±5%
- Output in constant voltage, ±5%
- Self-resetting protection against overtemperatures, open circuit and output short circuits.
- Input voltage: 110÷240V/AC - Steady output.

