

75
Watt


CV

PF
λ ≥ 0,96

IP 20

CE

EMC

M

M

F

ta-10°÷+40°C







84 mm


Dimmable


DMX
Dimmable


DALI
Dimmable

DT6



Part Number	Protocol	Output V	Output@230V I max 3ch	Output@230V I max 4ch	W @230V	W @110V	Dimensions A x B x C
A40RGBOX412B	DALI DT6 / DMX / PUSH	12V	3 x 2,08A	4 x 1,56A	75W	60W	210 x 75 x 35



Datasheet download

Convertitori per LED RGBW a 4 canali e RGB a 3 canali a 12V

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Ingresso pulsante bassa tensione. Comando della luce - accensione, regolazione e spegnimento con uno o più pulsanti
- Ingresso DMX e DALI con funzione auto-test incorporata e LED di segnalazione
- Configurabile per 3 o 4 canali di uscita
- Per LED di potenza RGBW e RGB a tensione costante. Uscita 4 x 12V PWM o 3 x 12V PWM 300Hz. Anodo comune.
- Collegamento in parallelo fino a max 10 x RGBox4
- Doppio morsetto
- Morsetti rapidi
- Pressacavo adatto a vari tipi di cavo, sia tondi che piatti
- Alimentazione: 110÷240 V/AC - Uscita stabilizzata
- A richiesta, alimentazione specifica a 110V (uscita potenziata)

12V driver for R G B W 4 channel and RGB 3 channel systems

- Independent driver - IP20 - Insulation class II
- Low voltage push button input. Light control - on, off and colour regulation by one or more push-buttons
- DMX and DALI inputs with self-test function and LED signal
- Configuration for 3 or 4 output channels
- Suitable for RGBW systems and constant voltage RGB systems. Output 4 x 12V PWM or 3 x 12V PWM 300Hz. Common anode
- Possible parallel connection up to 10 x RGBOX4 drivers
- Double terminal block
- Fast terminals
- Cable clamp for flat and round cables
- Input voltage: 110÷240 V/AC - Steady output.
- On request, specific boosted 110V version