

60/100  
Watt

  
CV

PF  
 $\lambda \geq 0,96$

IP 20



EMC





M

M

F

110

SELV


  
37 mm

$t_a -10^{\circ} \div +40^{\circ}C$

  
AC 50Hz

  
DC

On request



| Part Number  | Output<br>V | Output<br>Imax @ 230V | Output<br>Imax @ 110V | W<br>@230V | W<br>@110V | Dimensions<br>A x B x c |
|--------------|-------------|-----------------------|-----------------------|------------|------------|-------------------------|
| A40SLBOX060B | 24V         | 2,5A                  | 1,46A                 | 60W        | 35W        | 310 x 30 x 21           |
| A40SLBOX100B | 24V         | 4,16A                 | 2,08A                 | 100W       | 50W        | 310 x 30 x 21           |



Datasheet download

 **Alimentatore per moduli a LED**

- Alimentatore indipendente - IP20 - Classe II di isolamento
- Uscita in tensione costante,  $\pm 5\%$
- Alto fattore di potenza
- Protezione autoripristinante contro le sovratemperature, contro il circuito aperto ed i corto-circuiti sul secondario.
- Alimentazione: 110÷240V/AC - Uscita stabilizzata. A richiesta, alimentazione a 230VDC

 **Driver for LED modules**

- For independent use - IP20 - Insulation class II
- Steady voltage output,  $\pm 5\%$
- High power factor
- Self-resetting protection against overtemperatures, against open circuit and against output short circuits
- Input voltage: 110÷240V/AC - Steady output. On request, 230VDC input voltage

