

14
Watt/m

CRI>90

IP 20

III





$t_a -10^{\circ}\div +40^{\circ}\text{C}$







up to
85 lm/w

25 mm - 560 led/m
10 mm 

Part Number	CCT (K)	Lumen/m	Ra	LED/m	V (Typ)	Cut	W/m	IP	EEC*
A41ST24560CT	2700+6500K	1080+1190	94	280+280	24V/DC	25mm	14+14W	IP20	G

** The EEC specification refers in each case to the installed light source(s)



Datasheet download

 **ALIMENTATORI SUGGERITI:**
 **RECOMMENDED DRIVERS:**



Codice/Code: **A40PBX100TWB**
TW 24V Led Driver
Page:214

Strisce a LED 24V autoadesive TW IP20

- LED 2110 con ridotta spaziatura - Doppia fila
- Assenza di puntinatura anche con profili di basso spessore
- 280+280 led/m - 14+14W/m
- Tunable White 2700-6500K
- Fornite in nastro da 5m e cavetto di raccordo

24V adhesive LED strips TW IP20

- LED 2110 with reduced space among leds - Double line
- No dots visible even in very thin profiles
- 280+280 led/m - 14+14W/m
- Tunable White 2700-6500K
- Supplied in 5m reels with connecting cable