

RF
2.4GHzPF
 $\lambda \geq 0,6$

IP 40


CE

EMC

M

M

F

 $t_a -20^\circ \div +40^\circ\text{C}$ 

Part Number	Control	Application	Output	Dimensions A x B x C + D
A40WALLRGB2B	RGB	Single zone	2.4 GHz	86 x 86 x 32
A40WALLRGBWB	RGBW	Single zone	2.4 GHz	86 x 86 x 32
A40WALLCT20B	TUNABLE WHITE	Single zone	2.4 GHz	86 x 86 x 32
A40WALLDIM2B	DIMMER	Single zone	2.4 GHz	86 x 86 x 32



Datasheet download

Centralina radiocomando a tocco con uscita RGB / RGBW / Dimmer / Temperatura colore variabile

- Classe II di isolamento - Da incasso - IP40
- 2.4GHz
- Alimentazione: 230V AC
- Disponibile in 4 versioni: RGB, RGBW, Dimmer, controllo della temperatura del colore.
- Fornito con scatola plastica per fissaggio a muro o mobile

Touch RF Controller RGB / RGBW / Dimmer / Color Temperature Control

- Insulation class II - To be built in - IP40
- 2.4 GHz
- Input: 230V AC
- Available in 4 versions: RGB, RGBW, Dimmer, Color Temperature Control
- Wall box for built-in mounting available

